



PP FILTER

ฟิลเตอร์กรองน้ำยาเคมี แบบทั่วไป วัสดุเป็น PP

แบ่งออกเป็น 3 รุ่น

1. SA-SD Series ขนาดเล็ก สำหรับถึงขนาด 200-800 ลิตร
2. SK Series ขนาดกลาง สำหรับถึงขนาด 1000-3000 ลิตร
3. SL Series ขนาดใหญ่ สำหรับถึงขนาด 2500-7500 ลิตร

** ขนาดถังใส่เคมีที่ต้องการกรอง

** วัสดุ PP ควรใช้กับน้ำเคมีอุณหภูมิไม่เกิน 70 C'

เป็นอุณหภูมิแนะนำ แต่ตัว Mat. สามารถทนได้สูงสุดที่ 90 C'

** โปรดระวัง วัสดุ PP ไม่ได้ใช้ได้น้ำยาเคมีทุกความเข้มข้น และทุกชนิด ลูกค้าสามารถแจ้งเคมีที่ใช้งาน เพื่อที่เราจะได้ให้ คำปรึกษาได้

* If not sure with full strength test, or suggest: strong soap (MPS) control with detector of CYTO or PVP. The easiest simple pump is the best choice to prevent leak pollution on filling working or any leakage - or environmental pollution.
 * The filter medium use filter cartridge use pp3 storage with free of metal contact.
 * The filter provides high precision with wide filter area, high efficiency, easy operation.
 * Purchase accessories control (including special flow rate check valve, flow sensing tube or water level) at filter bag.

OPTIONAL

รุ่น	SA-SD	SK	SL	SL	SL	SL
ขนาดถัง (ลิตร)	200-800	1000-3000	2500-7500	2500-7500	2500-7500	2500-7500
ขนาดตัวกรอง (mm)	150	200	300	300	300	300
น้ำหนัก (กก.)	1.5	2.5	4.5	4.5	4.5	4.5
ราคา (บาท)	150	250	450	450	450	450

SA/SD SERIES



Features

Chemical liquid medicine filter

- One piece injected without welding of filter body and stand are adopted the integrative mould and increase the intensity of the filter body with the projection rib.
- According to the chemical density and temperature feature to inject the filter body. The material of filter body is made of PP, CPVC, or PVDF.
- The least welding of filter in filter field, it greatly decreases the leakage.
- With New design on Magnetic drive sealless pump, It can avoid the problems of dry running leakage and environment pollution.
- Motor guard which avoids the motor be corroded in acid environment.
- Excellent application to circulated filtering operations for plating liquid, chemical liquid and pure water.
- Filter cartridge type design, it provides high precision filtering with wide filter area, high efficiency, easy to operate and clean.
- Titanium (Ti) clamp set also can be provided as choice.
- Standard accessories: union of flange
- Purchase accessories: switch (including guard), foot valve, check valve, flow-seeing tube, in/outlet flexible, or filter bag, etc.

SA/SD SERIES

化學藥液過濾機

特點

- 過濾機桶身及腳座採用模具化生產方式一體成型，并在桶身形成增加強度的肋條。
- 過濾機桶身材質可為PP、CPVC、PVDF，依據液酸鹼濃度性質及溫度特性，直接射出成型。
- 過濾機焊點業界最少，大幅降低假性焊接洩漏之虞採用無縫封磁驅式泵浦，能有效的防止轉滲漏、污染環境等問題發生。
- 馬達防護罩確保馬達在酸氣中不易受腐蝕。
- 特別適用於電鍍液、化學液、純水藥液過濾等用途。
- 筒形式設計，高精度過濾，過濾面積廣，效率高，清洗容易。
- 另有款泵浦組可供選擇。
- 標準配件：出入口由任。
- 選購配件：開關（含護罩）、底閥或逆止閥、視液器、出入口軟管、濾袋等等。

型號說明

SA/SD - 104 - F - U - N - C - J - S - MP

1 2 3 4 5 6 7 8 9

1. 機型編號: SA/SD SERIES
2. 機型代號: 101-10"x1PCS, 102-10"x2PCS
201-20"x1PCS, 202-20"x2PCS
3. 濾桶材質: F-PP A-CPVC P-PVDF
4. 出入口型式: U-由任式
5. 密封材質: N-NBR V-VITON
6. 濾材材質: B-濾芯螺帽式
7. 出入口規格: J-JIS D-DIN A-ANSI
8. 東環組材質: S-SUS304 T-Ti
9. 泵浦型式: SMD Series-磁驅式

SA/SD系列規格

型式	SA-1001	SA-2001	SD-1004	SD-2004	
泵浦型式	SMD	SMD	SMD	SMD	
泵浦馬達(50/60Hz)	45W	65W	150/180W	255/265W	
濾材	濾芯螺帽式 B Type	10"x1	20"x1	10"x4	20"x4
	濾芯膠板式 C Type	-	-	-	-
	層疊濾芯式 T Type	-	-	-	-
	榻榻米濾布式 K Type	-	-	-	-
	濾紙式 P Type	-	-	129x23PCS	129x46PCS
袋濾式 U Type	-	-	-	-	
適用電鍍槽	200L	400L	600L	800L	
過濾量(L/Min)	15	30	60	80	
過濾面積(㎡)	濾芯式 B,C Type	0.125	0.25	0.5	1
	層疊濾芯式 T Type	-	-	-	-
	榻榻米濾布式 K Type	-	-	-	-
	濾紙式 P Type	-	-	0.3	0.6
袋濾式 U Type	-	-	0.5	1.0	
出入口徑 (inch)	3/4	3/4	1	1	
外型尺寸長x寬x高 (mm)	500x312x830	500x312x1100	573x360x900	573x360x1185	
機體重量 (Kg)	15	17	28	30	



Features

Chemical liquid medicine filter

- One piece injected without welding of filter body and stand are adopted the integrative mould and increase the intensity of the filter body with the projection rib.
- According to the chemical density and temperature feature to inject the filter body. The material of filter body is made of PP, CPVC, or PVDF.
- The least welding of filter in filter field, it greatly decreases the leakage.
- Assemble with self-priming pump or magnet drive pump is depending on customers. If with magnet drive pump, it can avoid the problems of dry running leakage and environment pollution.
- Motor guard which avoids the motor be corroded in acid environment.
- Excellent application to circulated filtering operations for plating liquid, chemical liquid and pure water.
- According to customer's requirement, various filter elements for choice and easy to operate: Lock Core Filter, Pressure Layered Core Filter, Bag Filter, Paper Filter, and Bellow Filter.
- The filter provides high precision with wide filter area, high efficiency, easy to operate and clean.
- Titanium (Ti) clamp set also can be provided as choice.
- Standard accessories: union of flange (including packing and PVC screws)
- Purchase accessories: switch (including guard), foot valve, check valve, flow-seeing tube, in/outlet flexible, or filter bag, etc.

化學藥液過濾機

特點

- 過濾機機身及腳座採用模具化學生產方式一體成型，并在桶身形成增加強度的肋條。
- 過濾機機身材質可選PP、CPVC、PVDF，依據液體濃度性質及溫度特性，直接射出成型。
- 過濾機焊點零數量少，大面積耐腐性焊接無滲漏之虞。
- 選擇性採用自吸式或磁驅式泵，其中無軸磁驅式泵能有效防止空轉泄漏、污染環境等問題發生。
- 馬達防護罩確保液體在酸氣中不易受腐蝕。
- 特別適用於電鍍液、化學液、純水過濾過濾等用途。
- 可依客戶不同需求之變化（濾心式、層疊濾心式、濾紙式、棉紙式、袋濾式）操作簡便。
- 高精度過濾，過濾面積廣，效率高，清洗容易。
- 另有鈦夾具組可供選擇。
- 標準配件：出入口法蘭（含墊片PVC螺絲）。
- 選擇配件：隔閥（含濾罩）、底閥或止回閥、視流器、出入口軟管、濾袋等等。

型號說明

SK - 206 - F - F - N - B - J - S - MPX

1 2 3 4 5 6 7 8 9

1. 機型編號: SK SERIES
2. 濾心數量: 206-20"x6PCS, 208-20"x8PCS
3. 濾桶材質: F-PP A-CPVC P-PVDF
4. 出入口型式: F-法蘭式
5. 密封材質: N-NBR V-VITON
6. 濾材型式: C-濾心壓板式 B-濾心螺帽式
T-層疊濾心壓板式 K-棉紙濾布式
P-濾紙式 U-袋濾式
7. 出入口規格: J-JIS D-DIN A-ANSI
8. 夾環組材質: S-SUS304 T-Ti
9. 泵浦型式: SLD-SLD SERIES(自吸式)
SPH-SPH SERIES(磁驅式)

SK系列規格

型 式	SK-206	SK-208-1	SK-208-2
泵浦型式	SLD/SPH	SLD/SPH	SLD/SPH
泵浦馬達(50/60Hz)	1/2-1HP	1HP	2HP
濾 材	濾心螺帽式 B Type	20"x6	20"x8
	濾心壓板式 C Type	20"x6	20"x8
	層疊濾心式 T Type	20"x6	20"x8
	棉紙濾布式 K Type	1SET	1SET
	濾紙式 P Type	195x45PCS	232x45PCS
袋濾式 U Type	Φ7"x16"L	Φ7"x16"L	Φ7"x16"L
適用電壓槽	1-2Ton	1-3Ton	1.5-3Ton
過濾量(L/Min)	150	180	220
過 濾 面 積 (㎡)	濾心式 B, C Type	1.5	2
	層疊濾心式 T Type	0.7	0.9
	棉紙濾布式 K Type	1.1	1.7
	濾紙式 P Type	1.5	2.2
	袋濾式 U Type	2.0	2.0
出入口徑(inch)	1.5	1.5/1.5"2	1.5/1.5"2
外型尺寸 長x寬x高(mm)	785x487x1510	785x487x1510	785x487x1510
機體重量(Kg)	70	77	77



Features

Chemical liquid filter

- One piece injected without welding of filter body and stand are adopted the integrative mould and increase the intensity of the filter body with the projection rib.
- According to the chemical density and temperature feature to inject the filter body. The material of filter body is made of PP, CPVC, or PVDF.
- The least welding of filter in filter field, it greatly decreases the leakage.
- Assemble with self-priming pump or magnet drive pump is depending on customers. If with magnet drive pump, it can avoid the problems of dry running leakage and environment pollution.
- Motor guard which avoids the motor be corroded in acid environment.
- Excellent application to circulated filtering operations for plating liquid, chemical liquid and pure water.
- According to customer's requirement, various filter elements for choice and easy to operate: Lock Core Filter, Pressure Layered Core Filter, Bag Filter, Paper Filter, and Bellow Filter.
- The filter provides high precision with wide filter area, high efficiency, easy to operate and clean.
- Titanium (Ti) clamp set also can be provided as choice.
- Standard accessories: union of flange (including packing and PVC screws)
- Purchase accessories: switch (including guard), foot valve, check valve, flow-seeing tube, in/outlet flexible, or filter bag, etc.

化學藥液過濾機

特點

- 過濾機桶身及底座採用模與化生產方式一體成型，并在桶身形成增加強度的肋條。
- 過濾機桶身材質可為PP、CPVC、PVDF，依藥液酸鹼濃度性質及溫度特性，直接射出成型。
- 過濾機焊點零界最少，大幅降低慢性滲漏之虞。
- 選擇性採用自吸式或磁驅式泵，其中無密封磁驅式泵能更有效防止空轉泄漏、污染環境等問題發生。
- 馬達防護罩確保在酸鹼中不易受腐蝕。
- 特別適用於電鍍液、化學液、純水高壓過濾等用途。
- 可依客戶不同濾材之變化（蓋心式、層疊蓋心式、蓋紙式、楊桃式、袋濾式）操作簡便。
- 高精密過濾，過濾面積廣，效率高，清洗容易。
- 另有結東選組可供選擇。
- 標準配件：出入口法蘭（含墊片PVC螺絲）。
- 選購配件：開關（含護罩）、底閥或截止閥、腳洗器、出入口軟管、濾袋等。

型號說明

SL - 206 - F - F - N - B - J - S - MPX

1 2 3 4 5 6 7 8 9

1. 機型編號: SL SERIES
2. 濾心數量: 212-20"x12PCS, 218-20"x18PCS
318-30"x18pcs
3. 濾桶材質: F-PP A-CPVC P-PVDF
4. 出入口型式: F-法蘭式
5. 密封材質: N-NBR V-VITON
6. 濾材型式: C-濾心壓板式 B-濾心線帽式
T-層疊濾心厚板式 K-楊桃濾布式
P-濾紙式 U-袋濾式
7. 出入口規格: J-JIS D-DIN A-ANSI
8. 束環組材質: S-SUS304 T-Ti
9. 泵浦型式: SLD-SLD SERIES(自吸式)
SPH-SPH SERIES(磁驅式)

SL系列規格

型式	SL-212	SL-218	SL-318
泵浦型式	SLD/SPH	SLD/SPH	SLD/SPH
泵浦馬達(50/60Hz)	2HP	3-5HP	3-5HP
濾材	濾心線帽式 B Type	20"x12	20"x18
	濾心壓板式 C Type	20"x12	20"x18
	層疊蓋心式 T Type	20"x12	20"x18
	楊桃濾布式 K Type	1SET	1SET
	蓋紙式 P Type	300x40PCS	370x40PCS
袋濾式 U Type	Φ7"x16"L	Φ7"x16"L	Φ7"x32"L
適用電壓槽	2.5-4Ton	4-6.5Ton	6-7.5Ton
過濾量(L/Min)	220	330-500	400-500
過濾面積(㎡)	蓋心式 B,C Type	3	4.5
	層疊蓋心式 T Type	1.3	2
	楊桃濾布式 K Type	2.4	4.4
	蓋紙式 P Type	3.6	5.4
	袋濾式 U Type	2.0	2.0
出入口徑(inch)	2/1.5"2	2	2
外型尺寸 長x寬x高(mm)	865x625x1555	865x625x1555	930x590x1767
機體重量(Kg)	97	177	125

PVDF FILTER

****SUPER
SPECIAL!!**



Features

Chemical liquid filter (PVDF)

- The filter housing body and its main spare part all adopt high quality PVDF material in one-body injection, it has feature with resistance to high temperature and high Acid and Alkali.
- It can work with Self-priming or magnetic drying pump with material of PVDF. The sealless magnetic pump is the best choice to prevent Such problems as Idling working or any leakage , or environmental pollution
- The filter medium use filter cartridge nut type design with free of metal contactant
- The filter provides high precision with wide filter area,high efficiency,
- Purchase accessories:switch (including guard),foot valve,check valve,flow-seeing tube,in/outlet flexible,or filter bag, etc.

PVDF MATERIAL

化學藥液過濾機 (PVDF材質)

特點

- 過濾機機身及各重要零件全採用生產，并以PVDF材質一體射出成型，具耐高溫及耐酸鹼等特性。
- 選擇性搭配自吸式或磁驅式泵浦，泵浦材質為PVDF，其中無軸封磁驅式泵浦能有效防止空轉洩漏、污染環境等問題發生。
- 濾材採用濾芯螺帽式設計，濾桶內完全無金屬接觸物。
- 高精度過濾、過濾面積廣、效率高、操作簡單。
- 選購配件：開關（含護罩）、底閥或逆止閥、視流器、出入口軟管、由任、法蘭、濾袋等等。

型號說明

SKX - 104 - P - U - V - B - J - S - MP
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

1. 機型編號: SKX SERIES
2. 機型代號: 101-10"x1PCS,102-10"x2PCS
201-20"x1PCS,202-20"x2PCS
104-10"x4PCS,204-20"x4PCS
206-20"x6PCS,208-20"x8PCS
212-20"x12PCS,218-20"x18PCS
3. 濾桶材質: P-PVDF
4. 出入口型式: U-由任式 F-法蘭式
5. 密封材質: V-VITON
6. 濾材材質: B-濾芯螺帽式
7. 出入口規格: J-JIS D-DIN A-ANSI
8. 束環組材質: S-SUS304 T-Ti
9. 泵浦型式: SLD-SLD SERIES (自吸式)
SMD-SMD SERIES (磁驅式)
SPH-SPH SERIES (磁驅式)

SKX系列規格

型 式	SKX-104	SKX-204	SKX-206	SKX-208	SKX-212	SKX-218	
泵浦型式	SMD	SMD	SLD/SPH	SLD/SPH	SLD/SPH	SLD/SPH	
泵浦馬達(150/60Hz)	255/265W	255/265W	1/2-1HP	1HP	2HP	3-5HP	
濾材	濾芯螺帽式 B Type	10"x4	20"x4	20"x6	20"x8	20"x12	20"x18
適用電壓槽	600L	800L	1-2Tom	1-3Tom	2.5-4Tom	4-6.5Tom	
過濾量(L/Min)	60	80	150	180	220	330-500	
過濾面積(m ²)	濾芯式 B Type	0.5	1	1.5	2	3	4.5
出入口徑 (inch)	1	1	1-1/2	1-1/2	2	2	
外型尺寸	長 (mm)	573	573	785	785	865	865
	寬 (mm)	360	360	487	487	625	625
	高 (mm)	900	1185	1510	1510	1555	1555
機體重量Weight (Kg)	26	30	70	77	97	117	

PVC FILTER

****SUPER SPECIAL**



Features

Chemical liquid filter(CPVC)

- The filter housing body and its main spare part all adopt high quality CPVC material in one-body injection, it has feature with resistance to high temperature and high Acid and Alkali.
- It can work with Self-priming(kb series) or magnetic drying pump (MPX series) with material of CPVC or PVDF. The sealless magnetic pump is the best choice to prevent Such problems as Idling working or any leakage , or environmental pollution
- The filter medium use filter cartridge nut type design with free of metal contactant
- The filter provides high precision with wide filter area,high efficiency,easy operation
- Purchase accessories:switch (including guard),foot valve,check valve,flow-seeing tube,in/outlet flexible,or filter bag,etc.

PVC MATERIAL

鉻酸過濾機(PVC材質)

特點

- 過濾機桶身及各零件採用PVC材質，具備耐酸鹼等特性。
- 選擇性搭配自吸式SLD SERIES或磁力驅動SPH SERIES泵浦，泵浦材質為PVDF，其中無軸封值驅式泵浦能有效的防止空轉泄漏、污染環境等問題發生。
- 濾材採用濾芯螺帽式設計，濾桶內完全無金屬接觸物。
- 高精度過濾、過濾面積廣、效率高、操作簡單。
- 選購配件：開關（含護罩）、底閥或逆止閥、視流器、出入口軟管、由任、法蘭、濾袋等等。

型號說明

SKT - 104 - A - U - V - B - J - S - MP
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

1. 機型編號: SKT SERIES
2. 機型代號: 101-10"x1PCS,102-10"x2PCS
201-20"x1PCS,202-20"x2PCS
104-10"x4PCS,204-20"x4PCS
206-20"x6PCS,208-20"x8PCS
212-20"x12PCS,218-20"x18PCS
3. 濾桶材質: A-CPVC
4. 出入口型式: U-由任式 F-法蘭式
5. 密封材質: V-VITON
6. 濾材材質: B-濾芯螺帽式
7. 出入口規格: J-JIS D-DIN A-ANSI
8. 束環組材質: S-SUS304 T-TI
9. 泵浦型式: SLD-SLD SERIES (自吸式)
SMD-SMD SERIES (磁驅式)
SPH-SPH SERIES (磁驅式)

SKT系列規格

型 式	SKT-104	SKT-204	SKT-206	SKT-208	SKT-212	SKT-218
泵浦型式	SMD	SMD	SLD/SPH	SLD/SPH	SLD/SPH	SLD/SPH
泵浦馬達(50/60Hz)	255/265W	255/265W	1/2-1HP	1HP	2HP	3-5HP
濾材	濾芯螺帽式 B Type	濾芯螺帽式 B Type	濾芯螺帽式 B Type	濾芯螺帽式 B Type	濾芯螺帽式 B Type	濾芯螺帽式 B Type
適用電壓槽	600L	800L	1-2Tom	1-3Tom	2.5-4Tom	4-6.5Tom
過濾量(L/Min)	60	80	150	180	220	330-500
過濾面積(m ²)	濾芯式 B Type	濾芯式 B Type	濾芯式 B Type	濾芯式 B Type	濾芯式 B Type	濾芯式 B Type
出入口徑 inch	1	1	1-1/2	1-1/2	2	2
外型尺寸	長 (mm)	573	573	785	785	865
	寬 (mm)	360	360	487	487	625
	高 (mm)	900	1185	1510	1510	1555
機體重量 (Kg)	28	30	70	77	97	117